

# Etch-2-Bond

Spray-On Etching Compound

## Specifications:

### Etch-2-Bond | Spray-On Etching Compound

 **1 Year Standard  
Manufacturer Warranty**

## Description

Etch-2-Bond is an eco-friendly, minimal VOC, salt-derived, concrete etching solution designed for application via spraying to condition hard troweled concrete surfaces. This etching product is engineered to interact with concrete, opening the pores of the concrete slab, which enhances the bond of surface coatings and the penetration of Hydro-Block Sealer. Etch-2-Bond plays a critical role in mitigating and preventing surface condensation from building up on hard troweled concrete surfaces and it creates a better slip resistance on burnished slabs.

## Limitations

Avoid application on concrete that has been previously treated with surface coatings, including but not limited to; paint, epoxy, adhesives, or any other permanent surface coatings. Never allow Etch-2-Bond to sit on finished surfaces in order to prevent potential discoloration.

## Surface Preparation

Enhance ventilation by opening all doors and windows surrounding the workspace to facilitate air circulation. When utilizing fans to enhance airflow, position them indirectly from the slab to prevent rapid evaporation of Etch-2-Bond. Thoroughly sweep the concrete surface with a broom to clear away dust and debris. Protect any finished areas/surfaces up to 2 feet above the concrete floor that is receiving Etch-2-bond with plastic sheeting to prevent any overspray.

## Application

Use a pump sprayer to evenly distribute a single layer of Etch-2-Bond onto the entire concrete surface, ensuring the surface is thoroughly saturated. The surface is thoroughly saturated when the concrete is darkened by the product. Let the product sit for 5-10 minutes on the surface. Following the application of Etch-2-Bond, proceed with a wet mop and a bucket of water or an auto scrubber to clean the surface, effectively removing any concrete dust created by the Etch-2-Bond.

## Spread

350 square feet per gallon.


## Warranty Information

Etch-2-Bond is backed by a 1-year manufacturer's limited warranty, which guarantees this product is devoid of defects. This warranty is confined to the replacement of the product by Concrete Moisture Mitigation in the event of a substantiated claim.

## Contact Information

For further inquiries or support regarding the Etch-2-Bond product or warranty, please reach out to Concrete Moisture Mitigation, Inc.

### Concrete Moisture Mitigation, Inc.


 [656]225-3330

 Info@Concreteemm.com

 7402 N 56th St, Suite 355, Tampa FL, 33617

 www.ConcreteMoistureMitigation.com

## WHY WE STAND OUT FROM OUR COMPETITORS



Last Revised: 11/11/2024

## Contact Us For More Information

Email: [Info@Concreteemm.com](mailto:Info@Concreteemm.com) • Address: 7402 N 56th Street, Suite 355, Tampa FL, 33617

